

Air Conditioning

Product Information

PUMY-P R410A
Inverter Heat Pump (12.5-22.4kW)
Multi-Split Units

Making a
World of
Difference

Multi-Splits



The **PUMY Series** allow up to 10 indoor units to be connected to a single outdoor unit, using the standard City Multi branch pipework system or via branch boxes and/or LEV kits to connect M Series or Mr Slim indoor units. This makes it an economic and efficient answer for multi-room applications, whilst also offering space saving benefits.

Key Features

- The condensing unit is extremely slimline which allows easy location and application of the system
- Connect stylish M Series wall mounted and floor mounted indoor units to the system via the LEV kit interface (PAC-LV11M)
- Connect M Series and Mr Slim indoor units via the PAC-MK-BC boxes alongside VRF indoor units to the same system



Cooling | Heating | Ventilation | Controls

Air Conditioning

Product Information

PUMY-P R410A Inverter Heat Pump (12.5-22.4kW) Multi-Split Units

Making a
World of
Difference




PUMY-P OUTDOOR UNITS		PUMY-P112VKM3	PUMY-P112YKM3	PUMY-P125VKM3	PUMY-P125YKM3	PUMY-P140VKM3	PUMY-P140YKM3	PUMY-P200YKM1
NUMBER OF CONNECTABLE INDOOR UNITS	Branch box / Mixed*1	8 / 10	8 / 10	8 / 10	8 / 10	8 / 10	8 / 10	8 / 10
CAPACITY (kW)	Heating (nominal)	14.0	14.0	16.0	16.0	18.0	18.0	25.0
	Cooling (nominal)	12.5	12.5	14.0	14.0	15.5	15.5	22.4
	Heating (UK)	11.6	11.6	13.3	13.3	14.9	14.9	25.0
	Cooling (UK)	11.5	11.5	12.9	12.9	14.3	14.3	18.5
COP / EER (NOMINAL)		4.61 / 4.48	4.61 / 4.48	4.28 / 4.05	4.28 / 4.05	4.03 / 3.43	4.03 / 3.43	4.28 / 3.70
SCOP / SEER		3.93 / 6.45	3.93 / 6.45	4.16 / 6.52	4.16 / 6.52	3.79 / 6.33	3.79 / 6.33	3.83 / 5.99
MAX AIRFLOW (m³/min)	Heating / Cooling	110	110	110	110	110	110	139
SOUND PRESSURE LEVEL (dBA)		49	49	50	50	51	51	56
SOUND POWER LEVEL (dBA)	Cooling	69	69	70	70	71	71	76
DIMENSIONS (mm)	Width x Depth x Height	1050 x 330+25 x 1338	1050 x 330+25 x 1338	1050 x 330+25 x 1338	1050 x 330+25 x 1338	1050 x 330+25 x 1338	1050 x 330+25 x 1338	1050 x 330+25 x 1338
WEIGHT (kg)		122	125	122	125	122	125	137
ELECTRICAL SUPPLY		220-240v, 50Hz	380-415v, 50Hz	220-240v, 50Hz	380-415v, 50Hz	220-240v, 50Hz	380-415v, 50Hz	380-415v, 50Hz
PHASE		Single	Three	Single	Three	Single	Three	Three
POWER INPUT (kW)	Heating/Cooling (nominal)	3.04 / 2.79	3.04 / 2.79	3.74 / 3.46	3.74 / 3.46	4.47 / 4.52	4.47 / 4.52	5.84 / 6.05
	Heating/Cooling (UK)	2.71 / 1.87	2.71 / 1.87	3.33 / 2.32	3.33 / 2.32	3.98 / 3.03	3.98 / 3.03	7.59 / 5.58
STARTING CURRENT (A)		14	7	14	7	14	7	7
RUNNING CURRENT (A)	Heating/Cooling [MAX]	12.86 / 11.80 [29.5]	4.98 / 4.57 [13.0]	15.82 / 14.64 [29.5]	5.78 / 5.35 [13.0]	18.91 / 19.12 [29.5]	6.55 / 6.62 [13.0]	8.74 / 9.05 [19.0]
FUSE RATING (BS88) - HRC (A)		1 x 32	1 x 16	1 x 32	1 x 16	1 x 32	1 x 16	1 x 20
PIPE SIZE MM (in)	Gas	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	15.88 (5/8")	19.05 (3/4")
	Liquid	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")	9.52 (3/8")	9.52 (3/8") ^{*2}
TOTAL PIPING LENGTH (m)	Branch box / Mixed*1	150 / 300 (240)	150 / 300 (240)	150 / 300 (240)	150 / 300 (240)	150 / 300 (240)	150 / 300 (240)	150 / 150 (150)
FURTHEST PIPING LENGTH (m)	(With no branch boxes)	80 (85)	80 (85)	80 (85)	80 (85)	80 (85)	80 (85)	80
BETWEEN BRANCH BOX AND OUTDOOR UNIT - LENGTH (m)		55	55	55	55	55	55	55
BETWEEN BRANCH BOX AND INDOOR UNIT - LENGTH (m)		25	25	25	25	25	25	25
BETWEEN INDOOR AND OUTDOOR UNIT - HEIGHT (m)		50m max ^{*3}	50m max ^{*3}	50m max ^{*3}	50m max ^{*3}	50m max ^{*3}	50m max ^{*3}	50m max ^{*3}
BETWEEN INDOOR AND INDOOR UNITS - HEIGHT (m)	Branch box / Mixed*1	12	12	12	12	12	12	12
CHARGE REFRIGERANT (kg) / CO ₂ EQUIVALENT (t) - R410A (GWP 2088)		4.8 / 10.0	4.8 / 10.0	4.8 / 10.0	4.8 / 10.0	4.8 / 10.0	4.8 / 10.0	7.3 / 15.2
MAX ADDITIONAL REFRIGERANT (kg) / CO ₂ EQUIVALENT (t) - R410A (GWP 2088)		13.7 / 28.6	13.7 / 28.6	13.7 / 28.6	13.7 / 28.6	13.7 / 28.6	13.7 / 28.6	13.5 / 28.2

Notes: *1 Branch box - only using branch boxes (PAC-MK) on the system. Mixed - using a mix of branch boxes (PAC-MK) and City Multi indoor units on the same system. Figure in brackets - when using 2 branch boxes.
*2 12.7mm (1/2") if furthest length ≥ 60m. *3 40m max if outdoor installed below.


PAC-MK - BRANCH BOX	PAC-MK31BC	PAC-MK51BC	PAC-LV - LEV KIT INTERFACE	PAC-LV11M
NUMBER OF CONNECTABLE INDOOR UNITS	3	5	NUMBER OF CONNECTABLE INDOOR UNITS	1
COMPATIBLE INDOOR UNITS	M Series, Mr Slim	M Series, Mr Slim	COMPATIBLE INDOOR UNITS	M Series
WEIGHT (kg)	6.7	7.4	CAPACITY INDEX OF INDOOR UNITS	15 to 50
DIMENSIONS (mm) Width x Depth x Height	450 x 280 x 170	450 x 280 x 170	WEIGHT (kg)	3.5
POWER SUPPLY TO	From outdoor unit	3 core + earth	DIMENSIONS (mm) Width x Depth x Height	355 x 142 x 138
BRANCH BOX*1	Separate supply	220-240v, 50Hz / Single Phase	ELECTRICAL SUPPLY	220-240v, 50Hz / Single Phase
	Separate supply fuse rating (BS88) - HRC (A)	6	FUSE RATING (BS88) - HRC (A)	6
POWER SUPPLY TO INDOOR UNITS	From branch box	3 core + earth		

PRODUCT DIMENSIONS


Upper View




Rear View



Side View



Front View



Side View

